

Dimmable Designer Elite LED PAR Lamps

12W ELITE DESIGNER DIMMABLE PAR30 (REPLACES 75W)



Item Number	ENERGY STAR®	Item Description	Voltage	Lamp Watts	Lumens	Lumens Per Watt	*CBCP	Beam Angle	CCT	CRI	STK/MT0	Case Quantity
LED12P30D24KFL		12W Smooth PAR30 - 2400K 40 Degree	120	12	800	66.7	1315	40	2400K	82	MT0	12
LED12P30D24KNFL		12W Smooth PAR30 - 2400K 25 Degree	120	12	800	66.7	2910	25	2400K	82	MT0	12
LED12P30D24KSP		12W Smooth PAR30 - 2400K 15 Degree	120	12	800	66.7	6155	15	2400K	82	MT0	12
LED12P30D27KFL		12W Smooth PAR30 - 2700K 40 Degree	120	12	800	66.7	1315	40	2700K	82	STK	12
LED12P30D27KNFL	★	12W Smooth PAR30 - 2700K 25 Degree	120	12	800	66.7	2910	25	2700K	82	STK	12
LED12P30D27KSP		12W Smooth PAR30 - 2700K 15 Degree	120	12	800	66.7	6155	15	2700K	82	MT0	12
LED12P30D30KFL		12W Smooth PAR30 - 3000K 40 Degree	120	12	825	68.8	1315	40	3000K	82	STK	12
LED12P30D30KNFL		12W Smooth PAR30 - 3000K 25 Degree	120	12	825	68.8	2910	25	3000K	82	STK	12
LED12P30D30KSP		12W Smooth PAR30 - 3000K 15 Degree	120	12	825	68.8	6155	15	3000K	82	MT0	12
LED12P30D35KFL		12W Smooth PAR30 - 3500K 40 Degree	120	12	850	70.8	1315	40	3500K	82	MT0	12
LED12P30D35KNFL		12W Smooth PAR30 - 3500K 25 Degree	120	12	850	70.8	2910	25	3500K	82	MT0	12
LED12P30D35KSP		12W Smooth PAR30 - 3500K 15 Degree	120	12	850	70.8	6155	15	3500K	82	MT0	12
LED12P30D41KFL		12W Smooth PAR30 - 4100K 40 Degree	120	12	875	72.9	1315	40	4100K	82	MT0	12
LED12P30D41KNFL		12W Smooth PAR30 - 4100K 25 Degree	120	12	875	72.9	2910	25	4100K	82	MT0	12
LED12P30D41KSP		12W Smooth PAR30 - 4100K 15 Degree	120	12	875	72.9	6155	15	4100K	82	MT0	12
LED12P30D50KFL		12W Smooth PAR30 - 5000K 40 Degree	120	12	875	72.9	1315	40	5000K	82	MT0	12
LED12P30D50KNFL		12W Smooth PAR30 - 5000K 25 Degree	120	12	875	72.9	2910	25	5000K	82	MT0	12
LED12P30D50KSP		12W Smooth PAR30 - 5000K 15 Degree	120	12	875	72.9	6155	15	5000K	82	MT0	12

12W ELITE DESIGNER DIMMABLE PAR30 SHORT NECK (REPLACES 75W)



LED12P30SD24KFL		12W Smooth PAR30 SN - 2400K 40 Degree	120	12	800	66.7	1315	40	2400K	82	MT0	12
LED12P30SD24KNFL		12W Smooth PAR30 SN - 2400K 25 Degree	120	12	800	66.7	2910	25	2400K	82	MT0	12
LED12P30SD24KSP		12W Smooth PAR30 SN - 2400K 15 Degree	120	12	800	66.7	6155	15	2400K	82	MT0	12
LED12P30SD27KFL		12W Smooth PAR30 SN - 2700K 40 Degree	120	12	800	66.7	1315	40	2700K	82	STK	12
LED12P30SD27KNFL	★	12W Smooth PAR30 SN - 2700K 25 Degree	120	12	800	66.7	2910	25	2700K	82	STK	12
LED12P30SD27KSP	★	12W Smooth PAR30 SN - 2700K 15 Degree	120	12	800	66.7	6155	15	2700K	82	MT0	12
LED12P30SD30KFL	★	12W Smooth PAR30 SN - 3000K 40 Degree	120	12	825	68.8	1315	40	3000K	82	STK	12
LED12P30SD30KNFL	★	12W Smooth PAR30 SN - 3000K 25 Degree	120	12	825	68.8	2910	25	3000K	82	STK	12
LED12P30SD30KSP	★	12W Smooth PAR30 SN - 3000K 15 Degree	120	12	825	68.8	6155	15	3000K	82	MT0	12
LED12P30SD35KFL	★	12W Smooth PAR30 SN - 3500K 40 Degree	120	12	850	70.8	1315	40	3500K	82	MT0	12
LED12P30SD35KNFL	★	12W Smooth PAR30 SN - 3500K 25 Degree	120	12	850	70.8	2910	25	3500K	82	MT0	12
LED12P30SD35KSP	★	12W Smooth PAR30 SN - 3500K 15 Degree	120	12	850	70.8	6155	15	3500K	82	MT0	12
LED12P30SD41KFL	★	12W Smooth PAR30 SN - 4100K 40 Degree	120	12	875	72.9	1315	40	4100K	82	MT0	12
LED12P30SD41KNFL	★	12W Smooth PAR30 SN - 4100K 25 Degree	120	12	875	72.9	2910	25	4100K	82	MT0	12
LED12P30SD41KSP		12W Smooth PAR30 SN - 4100K 15 Degree	120	12	875	72.9	6155	15	4100K	82	MT0	12
LED12P30SD50KFL		12W Smooth PAR30 SN - 5000K 40 Degree	120	12	875	72.9	1315	40	5000K	82	MT0	12
LED12P30SD50KNFL		12W Smooth PAR30 SN - 5000K 25 Degree	120	12	875	72.9	2910	25	5000K	82	MT0	12
LED12P30SD50KSP		12W Smooth PAR30 SN - 5000K 15 Degree	120	12	875	72.9	6155	15	5000K	82	MT0	12

★ ENERGY STAR® Rated (at time of print)



5 YEAR
WARRANTY

*Minimum CBCP est. Consult tcp.com for most current photometry and LM79 data.