



LED Lamp Specification

LED G16 Festive™ Globe Lamps

- 50,000 Hours average rated life. Use for decorative, restaurants, hotels, theatres and fequent start applications

Item #	Wattage	Description	Number of LED's	Intensity per LED (mcd)	Volts	Lumens	Base	M.O.L. (inches)	Diameter (inches)
LG1624VRD	1	LED Festive™, Red	10	2500	24	-	Medium	3.0	2.0
LG1624VBL	1	LED Festive™, Blue	10	1000	24	-	Medium	3.0	2.0
LG1624VGR	1	LED Festive™, Green	10	3000	24	-	Medium	3.0	2.0
LG1624VWH50K	1	LED Festive™, White, 5000K	10	2500	24	25	Medium	3.0	2.0
LG1624VAMB	1	LED Festive™, Amber	10	800	24	-	Medium	3.0	2.0
LG16C24VRD	1	LED Festive™, Red	10	2500	24	-	Candelabra	3.0	2.0
LG16C24VBL	1	LED Festive™, Blue	10	1000	24	-	Candelabra	3.0	2.0
LG16C24VGR	1	LED Festive™, Green	10	3000	24	-	Candelabra	3.0	2.0
LG16C24VWH50K	1	LED Festive™, White, 5000K	10	2500	24	25	Candelabra	3.0	2.0
LG16C24VAMB	1	LED Festive™, Amber	10	800	24	-	Candelabra	3.0	2.0
LG16120VRD	1	LED Festive™, Red	10	2500	120	-	Medium	3.0	2.0
LG16120VBL	1	LED Festive™, Blue	10	1000	120	-	Medium	3.0	2.0
LG16120VGR	1	LED Festive™, Green	10	3000	120	-	Medium	3.0	2.0
LG16120VTIV	1	LED Festive™, White Tivoli, 1900K	10	2500	120	15	Medium	3.0	2.0
LG16120VWH30K	1	LED Festive™, White, 3000K	10	2500	120	20	Medium	3.0	2.0
LG16120VWH50K	1	LED Festive™, White, 5000K	10	2500	120	25	Medium	3.0	2.0
LG16120VAMB	1	LED Festive™, Amber	10	800	120	-	Medium	3.0	2.0
LG16C120VRD	1	LED Festive™, Red	10	2500	120	-	Candelabra	3.0	2.0
LG16C120VBL	1	LED Festive™, Blue	10	1000	120	-	Candelabra	3.0	2.0
LG16C120VGR	1	LED Festive™, Green	10	3000	120	-	Candelabra	3.0	2.0
LG16C120VWH50K	1	LED Festive™, White, 5000K	10	2500	120	25	Candelabra	3.0	2.0
LG16C120VAMB	1	LED Festive™, Amber	10	800	120	-	Candelabra	3.0	2.0


Features and Benefits

- Long life: 50,000 hours
- Rated for continuous operation
- Excellent color consistency from bulb to bulb
- No need for frequent bulb replacements or relamping
- Excellent for rapid cycling applications


Specification

Input Line Voltage ----- 120VAC
 Input Line Frequency ----- 60HZ
 Lamp Life (rated) ----- 50,000 Hours
 Minimum Starting Temperature ----- -20 ' F
 Maximum Operating Temperature ----- 160 ' F
 U.L. / C.U.L. Listed ----- No
 Lamp Operating Frequency ----- 60 HZ
 Power Factor ----- > .90
 Total Harmonic Distortion ----- < 33%

5 YEAR
WARRANTY



Medium Base



Candelabra Base