

LED	25,000 Hours average rated life, 120 Volts
-----	--

Applications:

Ideal for applications where uniform multi-directional light output is required.

A Lamps:

- + Table Lamps
- + Floor Lamps
- + Sconces
- + Ceiling Fixtures



BR30s:

- ## + Downlights



PAR38s:

- + Track Lights
- + Downlights



Features	Benefits
Up to 85% less energy than halogen alternatives	Instant energy savings
Long life - 25,000 hours	Minimizes replacement and maintenance costs
Smooth, clean outside housing	Seemlessly blends into lighting applications.
UL approved for damp location	Can be used outdoors when protected from elements. Withstands humidity indoors/outdoors.
Shatter resistant	Lower the risk of injury and breakage



L10A19D27K



L10A19D0D27K



L10BR30D27K



LP381430KNDB

Catalog Number	
Notes	Type
	

Specifications

Input Line Voltage:	120 VAC
Input Power	See Chart
Input Line Frequency	50/60HZ
Lamp Life (Rated)	25,000 hrs
Minimum Starting Temp	-30°C
Maximum Operating Temp.....	40°C
CR1	82

Warranties and Certifications:	Item #	Lamp Type	Description	Voltage	Wattage	Incandescent Wattage Comparison	Lumens	LPW	CCT	CRI	M.O.L. (inches)	Diameter (inches)
3 YEAR WARRANTY* us *Based on 12 hours use per day	10W A Lamp											
	L10A19D27K	A19	10W A19 Dimming	120	10	60	800	81.6	2700	82	4.4"	2.4"
	10W A Lamp Omni											
	L10A19DOD27K	A19	10W A19 Dimming Omni	120	10	60	800	81.6	2700	82	4.4"	2.4"
	10W BR30											
	L10BR30D27K	BR	10W BR30 Dimming	120	10	65	650	66.3	2700	82	5.4"	3.8"
	14W PAR38											
	LP381430KNDB	PAR	14W PAR38 Non-Dimming	120	14	90	1,050	75.0	3000	82	5.3"	4.8"
For the most up-to-date specs, please visit www.tcpi.com												