

Order Information

SAMPLE ORDER NUMBER: **ML4DM10LSFL9FS1E - TL41RMW**

A complete luminaire consists of a fixture fitting + trim, order separately.

Fixture Fitting

Catalog Number	Description
ML4DM10LSFL9FS1E	4" Canless, Lumen Select(600/800/1000lms), 5CCT selectable, 90CRI, 40° optic, 120V, LE/TE 5% Dim
ML4DM10LSFL9FSE010	4" Canless, Lumen Select(600/800/1000lms), 5CCT selectable, 90CRI, 40° optic, 120-277V 0-10V 5% Dim
ML4DM08LSFL9F5F1E	4" Canless, Lumen Select(400/600/800lms), 5CCT selectable, 95CRI, 40° optic, 120V LE/TE 5% Dim
ML4DM06FLD2W1E	4" Canless, 600lms, Selectable D2W, 90CRI, 40° optic 120V LE/TE 5% Dim

Accessories

Accessories
<p>TIR4D25NFL = 25° narrow flood optic TIR4D40FL = 40° flood optic TIR4D55WFL = 55° wide flood optic TIR4D25AWW = 25° narrow flood asymmetric wall wash optic TIR45MH12PK = replacement media holder, package of 12 L100 Series = 2.0" lens and filters, see spec sheet HL4RSMF = 4" Mounting Frame (Round or Square)</p>

Trims

Shielding

Flange Finish

Trims	Shielding	Flange Finish
TL40R = 3-1/2" conical reflector ⁽⁸⁾	2G = Diffuse lens	MW = Matte white reflector and flange
TL41R = 2" round pinhole TL42S = 2" square pinhole	None	MW =Matte white flange MB =Matte black flange BN =Brushed nickel flange ORB =Oil rubbed bronze flange GB =German bronze flange BCu =Brushed copper flange
TL43R = 2" round lens pinhole TL44S = 2" square lens pinhole	2G = Diffuse lens	MWWB = Matte white flange, white lens frame MWBB = Matte white flange, black lens frame MBBB = Matte black flange, black lens frame BNBB = Brushed nickel flange, black lens frame ORBBB = Oil rubbed bronze flange, black lens frame GBBB = German bronze flange, black lens frame BCuBB = Brushed copper, black lens frame
TL45R = 2" round lens wall wash TL46S = 2" square lens wall wash	6G = Linear spread lens	MWWB = Matte white flange, white lens frame MWBB = Matte white flange, black lens frame
Notes (8) TL40R trim provides 1.15" lens regression to ML4 fixture.	Notes	Notes