



Advanced Features:

- Adjustable for Perfect Illumination
- Easy installation
- Long life LED
- Superior Heat Management
- Minimal UV or heat emitted on lit surface
- End to End connectivity up to 43W

Applications

- Indoor Use Only Display Case
- Cove Lighting
- Task Lighting
- Accent



Low Voltage LED Light Bar

Model #	Description	L2 (in.)
TLFLB32024	4-ft Slim Light Bar	48.07
TLFLB32018	3-Ft Slim Light Bar	36.25
TLFLB32012	2-Ft Slim Light Bar	24.43
TLFLB3207	1-Ft Slim Light Bar	12.61
Input Power	4.4W/linear foot	
Input Voltage	24VDC	
Power Supply	Low-Voltage Switching Mode Power Supply (Part # TLFLBPOWER-18)	
Operating Temp.	-20°C~40°C	
Colors Available:	3000K, 5500K, Red, Green, Blue	
Beam Angle Available	100°	
Lumen	180 lm/ft	
Life Rating	40,000hrs	
IP Rating	30	
Warranty	2-years	

Power Supply Part # TLFLBPOWER-18

Dimensions	4-1/8 x 1-7/8 x 1-1/8
Input	AC90-240V, 50/60Hz, plug and cord set
Output:	24VDC, up to 1.8A
Indoor Rated	cUL/UL listed

120-240V AC LED Light Bar

Model #	Description	L1 (in.)
TLALB455	4-ft Slim Light Bar 55°	47.32
TLALB355	3-Ft Slim Light Bar 55°	35.50
TLALB255	2-Ft Slim Light Bar 55°	23.68
TLALB155	1-Ft Slim Light Bar 55°	11.86
Dimensions	Overall Width 1.65" Overall Height 1.54"	
Input Power	6W/linear foot	
Input Voltage	100-240V AC, 50/60Hz	
Operating Temp.	-20°C~40°C	
Colors Available:	3000K, 5500K, Red, Green, Blue	
Beam Angle Available	55° (100° optional)	
Lumen	245 lm/ft	
Life Rating	40,000hrs	
IP Rating	30	
Warranty	2-years	



*ADD COLOR TEMPERATURE CCT (K) REQUIRED TO ITEM NUMBER WHEN ORDERING:

EXAMPLE: TLFLB32012-CW CW=5500 WW=3000

