

TOMAR-700-110-A



Key Features

- Aluminum housing
- Heavy duty construction
- Solid state power supply
- Xenon strobe lamp
- Colors: amber, blue, clear, green, purple, & red
- 2 year warranty on power supply
- 1 year warranty on lamp
- UL recognized (DC models only)
- NEMA 3R

Models

- 700–110–15J AC strobe, 15 joule 120VAC, 50/60HZ
- 700–110 AC strobe 120VAC, 50/60HZ
- 700–240 AC strobe 240VAC, 50/60HZ
- 700–1274 DC strobe, UL recognized 12 – 74VDC
- 700–120DC DC strobe, UL recognized 120VDC

Specs

- Flash Rate 80 to 95 flashes per minute
- Light Output 185 effective candlepower (ECP)* (8 Joules model) 360 effective candlepower (ECP)* (15 Joules model)
- Voltage and Amperage 12-74VDC draws 1.25 A average @ 12VDC tapering to draws 0.2A average @ 74VDC
- 120VAC draws 0.17A average
- 120VDC draws 0.1A average
- 240VAC draws 0.12A average
- Power Supply Output 11 Watts 8 joules model per flash. 800,000 peak candlepower**
- 15 joules model per flash. 1,500,000 peak candlepower**
- Size and Weight 6" tall x 4.7" dia. x 1.3 lbs (152mm x 119mm x 0.58kg)