

TP Series

LED Vapor Tight



Features

Housing

Injection Molded Polycarbonate
Suitable for Ceiling Mount or Suspended Mount

Optical

Shade: Injection Molded High Transmission Opal Polycarbonate Creates Excellent Light Distribution and Uniformity
High Luminous Efficacy > 110 lm/W

Electrical

Built-in Constant Current LED Driver with High efficient LED Module
-BI: Bi-Level Light Option

Lamp

Built-in LED Module

Certification

UL/cUL Listed, Suitable for Damp Locations, DLC Listed

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L X W X H)	DLC
TP20W-2FT-3000K	120V ~ 277V	20W	3000K	82	2330	23.6" x 3.7" x 2.4"	Yes
TP20W-2FT-4000K	120V ~ 277V	20W	4000K	82	2330	23.6" x 3.7" x 2.4"	Yes
TP20W-2FT-5000K	120V ~ 277V	20W	5000K	82	2400	23.6" x 3.7" x 2.4"	Yes
TP36W-4FT-3000K	120V ~ 277V	36W	3000K	82	4230	47.2" x 3.7" x 2.4"	Yes
TP36W-4FT-4000K	120V ~ 277V	36W	4000K	82	4400	47.2" x 3.7" x 2.4"	Yes
TP36W-4FT-5000K	120V ~ 277V	36W	5000K	82	4600	47.2" x 3.7" x 2.4"	Yes
TP45W-4FT-3000K	120V ~ 277V	42.5W	4000K	82	5000	47.2" x 3.7" x 2.4"	Yes
TP45W-4FT-4000K	120V ~ 277V	42.5W	4000K	82	5000	47.2" x 3.7" x 2.4"	Yes
TP45W-4FT-5000K	120V ~ 277V	42.5W	5000K	82	5300	47.2" x 3.7" x 2.4"	Yes
TP70W-8FT-3000K	120V ~ 277V	70W	4000K	82	7900	94.5" x 3.7" x 2.4"	Yes
TP70W-8FT-4000K	120V ~ 277V	70W	4000K	82	7900	94.5" x 3.7" x 2.4"	Yes
TP70W-8FT-5000K	120V ~ 277V	70W	5000K	82	8400	94.5" x 3.7" x 2.4"	Yes