


BAYONET & SPECIAL SOCKETS

Halogen G8 Socket & Bulbs

250V-100W

A. G8F4

B. G8F6




Flange Mounting Halogen

A. L554 - FRONT FLANGE

B. L555 - REAR FLANGE

200° wire, 3000W-600V
with 18" leads




Quartz Bayonet Sockets Double Contact

A. L910-200 - Mounting Bracket

B. L910-001 - 1/8 IPS Male Bushing

18 ga. 200° wire, 500W-125V
with 9" leads



Single & Double Contacts

A. L905 - Single Lead

B. L905B - Double Contact

C. L905-2 - Double Lead

Low Voltage Applications with 9" leads



G9 Socket & Barrel

A. LB258301

B. LB259303

rear push wire contacts, screw or
snap-in mount, 1/8 IP threaded
barrel, ceramic socket



GU10 Socket

A. GU10PH
(1/8 IP hickey)

B. GU10P
(bottom leads)

6" high temp leads, 100W-250V



Halogen R7S Socket

LWR7S

200° wire, 500W-250V, Nickel plated brass
with 6" leads



Porcelain Body

LDA005

UL, 1000W-250V, G4.0 / G5.3 / G6.35
with 6" leads



Metal Halide Lamps with G12 Base

Cat. No. 557 porcelain lampholder
is designed for single-ended metal
halide lamps with a G12 base, rated
up to 150 watts. Standard leads (2)
are White, No. 18 AWG SEW-2 200°C
600V wire, 12" long, stripped 1/2".

Ideal for indoor accent and display
lighting, including gallery, museum
and showroom applications

Cat. No. 557
660W-600V 5KV PULSE RATED



High Pressure Sodium Lamps with PG-12 Base

Cat. No. 558 porcelain lampholder is
designed for high-pressure sodium
lamps with a PG-12 base, such as the
Philips SDWT-T 35-50- and 100-watt
White Son lamps. Standard leads, one
Red (pulse) and one Blue, are No. 18
AWG SEW-2 200°C 600V wire, 12"
long, stripped 1/2".

These lamps provide excellent bright-
ness and color rendition for galleries,
museums, showrooms and other ac-
cent and display light applications.

Cat. No. 558
660W-600V 5KV PULSE RATED

