

PHENOLIC INCANDESCENT SOCKETS

Pull Chain with Outlets

- A. L1406B - Black B. L1406-Ivory
250W 125V



- A. (T1) Keyless 660W-250V
B. (T2) Pull Chain 250W-250V
C. (T3) 3-Way 250W-250V
D. (T4) Single Circuit 250W-250V

Ring 2-1/8" O.D. included, socket height
2-5/8", socket thread slips
1-3/8" minimum, 1/8" IP



CANDELABRA SOCKETS

Hickey Sockets

75W-125V leads-18ga.

L150-2

1-3/4" High 24"
Leads, 150 C°

L10017-62F

1-3/4" High Leads
24", 105 C°

L10017-241F

3" High Leads
24", 105 C°

L10017-204F

4" High Leads
24", 105 C°



Porcelain with Screw Terminals

approved for 170 C° applications
75W-125V

L20025 -height 2-3/32"

Adjustables

A. L20026 -3-1/2"- 4-5/8"

B. L20026-2 -4-1/2"-5-1/2"



Twin Cluster LD1019

3-1/4" end to end 1/8 IPS tapped
bracket 75W-125V



Candelabra Phenolic Socket

Sockets have Screw Terminals
Insulators included 75W 125V

A. L10027 -1-3/4" High domestic

B. L10025 -Height 2" domestic

B1. L10025-2 - Height 2" import

C. L10026 -domestic

C1. L10026-2 - import



Adjustable
3-1/2" to 4-5/8"

Harness Set

L10032-500

75W-250V

1 to 500 cut to order 13"
center to center



Threaded Body Sockets Candelabra

L10032F

Plastic Nut Included



Molded Plastic Nut BA23569

