



16200 S. Figueroa St., Gardena, Ca 90248
 Tel: 310-324-8880 Fax: 310-324-4020
 www.sunparkelectronics.com
 e-mail: info@sunpkco.com



- * UL/ cUL Listed
- * Sound Rating - Class A
- * Ballast Factor - Great than 0.88
- * Meets FCC Part 18C, Class A
- * Outdoor Type 1
- * No PCB's
- * Crest Factor - Less than 1.70
- * Power Factor (P.F) - > 0.99
- * THD < 10%
- * NEMA PREMIUM & CEE Listed

3.4.2010

High Efficient Electronic Ballast Specifications

Ballast Models	Lamps		Input (Nom.)			Operation Frequency	Starting Temp.	Ballast Factor	Dimensions				Efficacy	
	Type	Qty	Voltage	Power	P. F				THD(max)	L	W	H		Mtg Ctr.
U-2/32IS	2 x 32W T8	2	120V / 277V	55.7	> 0.99	10%	> 42 KHz	- 20 F	0.89	9.50"	1.50"	1.12"	8.91"	1.60
U-3/32IS HPF	3 x 32W T8	3	120V / 277V	82.9	> 0.99	10%	> 42 KHz	- 10 F	0.885	9.50"	1.50"	1.12"	8.91"	1.07
U-4/32IS HPF	4 x 32W T8	4	120V / 277V	109	> 0.99	10%	> 42 KHz	- 10 F	0.884	9.50"	1.50"	1.12"	8.91"	0.81
U-2/32IS HBF	2 x 32W T8	2	120V / 277V	74.9	> 0.99	10%	> 42 KHz	- 20 F	1.166	9.50"	1.50"	1.12"	8.91"	1.56
U-3/32IS HBF	3 x 32W T8	3	120V / 277V	109.8	> 0.99	10%	> 42 KHz	- 10 F	1.17	9.50"	1.50"	1.12"	8.91"	1.07
U-4/32IS HBF	4 x 32W T8	4	120V / 277V	148.9	> 0.99	10%	> 42 KHz	- 10 F	1.17	9.50"	1.50"	1.12"	8.91"	0.79
U-4/32IS LBF	4 x 32W T8	4	120V / 277V	97.2	> 0.99	10%	> 42 KHz	- 10 F	0.78	9.50"	1.50"	1.12"	8.91"	0.80
U-2/32ISE	2 x 32W T8	2	120V / 277V	54	> 0.99	10%	> 42 KHz	- 20 F	0.89	9.50"	1.50"	1.12"	8.91"	1.65
U-3/32ISE	3 x 32W T8	3	120V / 277V	83	> 0.99	10%	> 42 KHz	- 10 F	0.88	9.50"	1.50"	1.12"	8.91"	1.06
U-4/32ISE	4 x 32W T8	4	120V / 277V	108	> 0.99	10%	> 42 KHz	- 10 F	0.88	9.50"	1.50"	1.12"	8.91"	0.81
U-2/32ISE-HBF	2 x 32W T8	2	120V / 277V	73	> 0.99	10%	> 42 KHz	- 20 F	1.18	9.50"	1.50"	1.12"	8.91"	1.62
U-3/32ISE-HBF	3 x 32W T8	3	120V / 277V	106	> 0.99	10%	> 42 KHz	- 10 F	1.18	9.50"	1.50"	1.12"	8.91"	1.11
U-4/32ISE-HBF	4 x 32W T8	4	120V / 277V	144	> 0.99	10%	> 42 KHz	- 10 F	1.16	9.50"	1.50"	1.12"	8.91"	0.81
U-2/32ISE-LBF	2 x 32W T8	2	120V / 277V	48	> 0.99	10%	> 42 KHz	- 20 F	0.78	9.50"	1.50"	1.12"	8.91"	1.63
U-3/32ISE-LBF	3 x 32W T8	3	120V / 277V	74	> 0.99	10%	> 42 KHz	- 10 F	0.78	9.50"	1.50"	1.12"	8.91"	1.05
U-4/32ISE-LBF	4 x 32W T8	4	120V / 277V	96	> 0.99	10%	> 42 KHz	- 10 F	0.77	9.50"	1.50"	1.12"	8.91"	0.80
U-2/32PSE	2 x 32W T8	2	120V / 277V	56	> 0.99	10%	> 42 KHz	- 20 F	0.88	9.50"	1.50"	1.12"	8.91"	1.57

U-2/32PSE-HBF	2 x 32W T8	2	120V / 277V	71.6	> 0.99	10%	> 42 KHZ	- 20 F	1.15	9.50"	1.50"	1.12"	8.91"	1.61
---------------	------------	---	-------------	------	--------	-----	----------	--------	------	-------	-------	-------	-------	------