

SUNPARK-U-4/32ISE-HBF

SPECIFICATIONS

- Type: Electronic Fluorescent
- Start Method: Instant Start
- Lamps: four F32T8
- Input Voltage: Multi Volts 120-277V

FEATURES

- Crest Factor: 1.70
- Sound Rated Class A
- 99% power factor
- 5 years warranty

DIMENSIONS

- Length: 9.50"
- Height: 1.13"
- Width: 1.63"
- Mounting Height: 8.91"

Compliance

- UL & cUL Listed
- Class P, Type 1 Outdoor
- FCC Class B

	NEMA Premium & CEE Listed Ballasts	CEE Listed High Performance Electronic Ballast for <i>Reduced Wattage T8 Lamps</i>
1. Input Voltage	120 V ~ 277V	120 V ~ 277V
2. Lamp Qty	4	4
3. Lamp Type	F32T8, 32W / F32T8 ES, 30W FB32/31/28 T8, F25T8, 25W / F17T8, 17W	F28T8, 28W F25T8, 25W
4. Input Watts	144W	115W / 109W
5. Line Amps	1.21A	0.97A / 0.92A
6. Power Factor	>0.99	>0.99
7. THD	< 10%	< 10%
8. Ballast Factor	1.16	1.16
9. BEF	0.81	1.01 / 1.06
10. Min Start Temperature	-10 °F	-10 °F
11. Length	9.50 inch	9.50 inch
12. Width	1.63 inch	1.63 inch
13. Height	1.13 inch	1.13 inch
14. Mounting Center	8.91 inch	8.91 inch