

SYLVANIA Luminaires

ValueLED™ UFO High Bay

Application

An environmentally preferable alternative to traditional luminaires and offering up to 78% energy savings, the ValueLED UFO High Bay is ideal for illuminating warehouses, gymnasiums, and other industrial applications.

Benefits and Features

- Lightweight fixture is designed for easy and safe installation
- Multiple mounting options for a variety of applications – pendant, hook, surface mount
- Mounting hook and mounting bracket included
- Variety of optics – polycarbonate refractor and aluminum reflector available
- IP65 rated aluminum body (finish is white)
- Tempered glass lens
- Up to 135 LPW
- 3500K, 4000K and 5000K color temperatures
- CRI >80
- Offered in 100, 150, 200, and 240 watts

Electrical

- Designed to operate through 120-277V (UNV) or 347-480 (HUV) V_{AC} voltage
- Power Factor >90%
- THD <20%
- 0-10V dimming
- Constant current LED driver with 4kV surge suppression

Rated Life

- ≥150,000 hours (L₇₀) @25°C

Warranty

- 5-year

Ambient Operating Range

- -40°F to +122°F (-40°C to +50°C) (100, 150 and 200W versions)
- -40°F to +113°F (-40°C to +45°C) (240W versions)

Certifications and Listings

- cULus
- RoHS
- FCC
- DLC Premium

Item #

Type

Project

Notes

Date



Wattage Comparison

Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings
250W MH	290	100	66%
250W HPS	295	100	66%
320W MH	370	150	59%
400W HPS	460	150	67%
400W MH	450	150	67%
750W MH	820	200	76%
750W HPS	840	200	76%
1000W MH	1080	240	78%
1000W HPS	1100	240	78%

Installation

- Luminaire mounting options include hanging via hook, surface mounting, or pendant mounting with included mounting bracket.
- Aluminum reflector, polycarbonate refractor, and polycarbonate bottoms lens also available.
- Includes 6' power cable and 3' dimming cable.



LEDLUM060R4 3-20



Ordering Guide

UFOHIBA	1A	/	XXX	XXX	D	8	XX	/	WH
Product Name	Generation		Wattage	Voltage	Dimming	CRI	Color Temp (CCT)		Color/Finish
UFOHIBA =	1A		100 = 100 Watts	UNV = 120-277V	D = 0-10V	8 = >80	35 = 3500K		WH = White
UFO High Bay			150 = 150 Watts	HUV = 347-480V			40 = 4000K		
			200 = 200 Watts				50 = 5000K		
			240 = 240 Watts						


Ordering Information

Item Number	Ordering Abbreviation	Wattage	Input Voltage	Dimming	CRI	Color Temp	Total Fixture Lumens (with Refractor Accessory)		Total Fixture Lumens (with Reflector Accessory)		DLC	 MTO*
							LPW		LPW			
61121	UFOHIBA1A/100UNVD835/WH	100	120-277	0-10	>80	3500K	13,800	133	13,100	126	Prm	MTO
61122	UFOHIBA1A/100UNVD840/WH	100	120-277	0-10	>80	4000K	13,800	133	13,100	126	Prm	
61123	UFOHIBA1A/100UNVD850/WH	100	120-277	0-10	>80	5000K	13,800	133	13,100	126	Prm	
61124	UFOHIBA1A/150UNVD835/WH	150	120-277	0-10	>80	3500K	20,300	135	19,200	127	Prm	MTO
61125	UFOHIBA1A/150UNVD840/WH	150	120-277	0-10	>80	4000K	20,300	135	19,200	127	Prm	
61126	UFOHIBA1A/150UNVD850/WH	150	120-277	0-10	>80	5000K	20,300	135	19,200	127	Prm	
61127	UFOHIBA1A/200UNVD835/WH	200	120-277	0-10	>80	3500K	26,000	130	26,000	127	Prm	MTO
61128	UFOHIBA1A/200UNVD840/WH	200	120-277	0-10	>80	4000K	26,000	130	26,000	127	Prm	
61129	UFOHIBA1A/200UNVD850/WH	200	120-277	0-10	>80	5000K	26,000	130	26,000	127	Prm	
61130	UFOHIBA1A/240UNVD835/WH	240	120-277	0-10	>80	3500K	31,300	132	30,300	127	Prm	MTO
61131	UFOHIBA1A/240UNVD840/WH	240	120-277	0-10	>80	4000K	31,300	132	30,300	127	Prm	
61132	UFOHIBA1A/240UNVD850/WH	240	120-277	0-10	>80	5000K	31,300	132	30,300	127	Prm	
61133	UFOHIBA1A/100HUV835/WH	100	347-480	0-10	>80	3500K	13,800	133	13,100	126	Prm	MTO
61134	UFOHIBA1A/100HUV840/WH	100	347-480	0-10	>80	4000K	13,800	133	13,100	126	Prm	
61135	UFOHIBA1A/100HUV850/WH	100	347-480	0-10	>80	5000K	13,800	133	13,100	126	Prm	
61136	UFOHIBA1A/150HUV835/WH	150	347-480	0-10	>80	3500K	20,300	135	19,200	127	Prm	MTO
61137	UFOHIBA1A/150HUV840/WH	150	347-480	0-10	>80	4000K	20,300	135	19,200	127	Prm	
61138	UFOHIBA1A/150HUV850/WH	150	347-480	0-10	>80	5000K	20,300	135	19,200	127	Prm	
61139	UFOHIBA1A/200HUV835/WH	200	347-480	0-10	>80	3500K	26,000	130	26,000	127	Prm	MTO
61140	UFOHIBA1A/200HUV840/WH	200	347-480	0-10	>80	4000K	26,000	130	26,000	127	Prm	
61141	UFOHIBA1A/200HUV850/WH	200	347-480	0-10	>80	5000K	26,000	130	26,000	127	Prm	
61142	UFOHIBA1A/240HUV835/WH	240	347-480	0-10	>80	3500K	31,300	132	30,300	127	Prm	MTO
61143	UFOHIBA1A/240HUV840/WH	240	347-480	0-10	>80	4000K	31,300	132	30,300	127	Prm	
61144	UFOHIBA1A/240HUV850/WH	240	347-480	0-10	>80	5000K	31,300	132	30,300	127	Prm	


*Made To Order

Photometric Data

Polycarbonate Refractor




Isofootcandle Lines at 20' Mounting Height




Isofootcandle Lines at 20' Mounting Height


Aluminum Reflector




Isofootcandle Lines at 20' Mounting Height




Isofootcandle Lines at 20' Mounting Height




Isofootcandle Lines at 20' Mounting Height




Isofootcandle Lines at 20' Mounting Height




Isofootcandle Lines at 30' Mounting Height




Isofootcandle Lines at 30' Mounting Height




Isofootcandle Lines at 30' Mounting Height



Isofootcandle Lines at 30' Mounting Height




Isofootcandle Lines at 30' Mounting Height



Isofootcandle Lines at 30' Mounting Height


Physical Information

Luminaire Description	Diameter	Height
100W/150W	11.7"	9.0"
200W/240W	14.2"	9.9"



Accessories

Item Number	Ordering Abbreviation	Item Description
61428	UFOHIBA1A/PC1/T5	Polycarbonate refractor for 100 and 150W (type V distribution)
61429	UFOHIBA1A/PC2/T5	Polycarbonate refractor for 200 and 240W (type V distribution)
61430	UFOHIBA1A/AL1/90	Aluminum reflector for 100 and 150W (90° beam angle)
61431	UFOHIBA1A/AL2/90	Aluminum reflector for 200 and 240W (90° beam angle)
61432	UFOHIBA1A/BOTTOMLENS	Polycarbonate bottom lens



LEDVANCE LLC
 200 Ballardvale Street
 Wilmington, MA 01887 USA
 Phone 1-800-LIGHTBULB (1-800-544-4828)
www.sylvania.com

SYLVANIA and LEDVANCE are registered trademarks.
 All other trademarks are those of their respective owners.
 Licensee of product trademark SYLVANIA in general lighting.
 Specifications subject to change without notice.



Name: _____
 Email: _____
 Phone: _____

