

ULTRA-ARC™ METAL HALIDE

METAL HALIDE LAMPS FOR HPS RETROFIT

USHIO Ultra-Arc™ Metal Halide lamps feature the best combination of color balance and color rendering quality available for a direct retrofit into High Pressure Sodium fixtures.

The Ultra-Arc lamps are used in High Pressure Sodium fixtures where the high color rendering, and white light of metal halide is desired. Ideal for areas where security is a concern - higher color rendering lamps allow for surveillance/security cameras and eyewitnesses to visually interpret in true colors.

Available in - T15, E39 mogul base
250W and 400W with a color temperature of 5200K

HIGH PRESSURE SODIUM		METAL HALIDE
LU250 ED18	→	UHI-S250DD, T15
LU400 ED18	→	UHI-S400DD, T15
22 CRI	→	85 CRI
2100K	→	5200K
Ballast		Ballast
S50 - 250W; S51 - 400W	→	S50 - 250W; S51 - 400W

FEATURES & BENEFITS:

- High Pressure Sodium Retrofit - No Need to Change Ballast and Ignitor
- High Color Temperature - 5200K
- Excellent Color Rendering - 85 CRI
- High Color Stability
- Long Life - Up to 20,000 Hours Average Life



UltraArc™ Metal Halide lamps are manufactured under ISO 9001 guidelines ensuring quality and security for the purchaser.



USHIO

APPLICATIONS:

- Security
- Parking Structures and Lots
- Downlighting
- Commercial and Industrial
- Walkways
- Bus Stops
- Pedestrian Areas



Metal Halide Lamps for HPS Retrofit



Sold in Case Quantity Only (12/case)

Watts (W)	Ordering Code	Lamp Description	Lamp Current (A)	Arc Gap (mm)	Color Temp (K)	CRI	Luminous Flux (lm)	Mean Luminous	Average Life (h)		ANSI Ballast / Fixture
									Vert. Burn Position	Hor. Burn Position	
ULTRA-ARC™ Mogul Screw Base											
250	5001175	UHI-S250DD	3.0	24	5200	85	20000	14000	15000	10000	S50/E*
400	5000798	UHI-S400DD	4.6	27	5200	85	33000	23000	20000	15000	S51/E*

*Use with ignitor All dimensions shown in inches unless otherwise noted.

Burn Cycle:
11 hours ON and 1 hour OFF (Recommended shut down 15 minutes per week)

Recommended Ignition Voltage: 2kV
ANSI Fixture Requirement:
/E = Enclosed fixture required

R - NON SELF-EXTINGUISHING LAMP
WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. Complies with the USA Federal Standard 21 CFR 1040.30 and Canada Standard SOR/80-381.

(Hg) - LAMP CONTAINS MERCURY
Manage in Accord with Disposal Laws
See: www.lamprecycle.org or 1-800-895-8842