

# ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer



Ahmed Eissa

# ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer

## Key Features and Benefits



### Applications

- Offices
- Retail Spaces
- Multipurpose Rooms
- Hospitality Areas

- Application : The ValueLED Retrofit Doorkit and Volumetric Troffer are offered in three sizes (1'x4', 2'x2', and 2'x4'). The addition of the 1'x4' options fills an existing gap in our current portfolio
- All models are DLC Premium listed to maximize rebate opportunities
- The lumen selectability feature allows for a wide range of lumen output options with fewer NAEDs, reducing the complexity of inventory management

Dimensions	Wattage	CCT	Lumens	Warranty
1x4	20, 25, or 30	3500, 4000, or 5000	2500, 3125, or 3750	5 years
2x2	20, 25, or 30	3500, 4000, or 5000	2500, 3125, or 3750	5 years
2x4	25, 30, or 34	3500, 4000, or 5000	3100, 3750, or 4250	5 years
2x4	34, 38, or 45	3500, 4000, or 5000	4250, 4750, 5600	5 years



## ValueLED™ Lumen Selectable Retrofit Doorkit Product Offering

Item Number	Ordering Abbreviation	Wattage	Voltage	Dimming	CRI/CCT	Lumens	LPW	Lifetime	Option
61525	<a href="#">RDORKIT5AS/030UNVD835/22U/WH</a>	20, 25 or 30	120-277	0-10	835	2500, 3125 or 3750	125	≥50,000	-
61526	<a href="#">RDORKIT5AS/030UNVD840/22U/WH</a>	20, 25 or 30	120-277	0-10	840	2500, 3125 or 3750	125	≥50,000	-
61527	<a href="#">RDORKIT5AS/030UNVD850/22U/WH</a>	20, 25 or 30	120-277	0-10	850	2500, 3125 or 3750	125	≥50,000	-
61528	<a href="#">RDORKIT5AS/034UNVD835/24U/WH</a>	25, 30 or 34	120-277	0-10	835	3100, 3750 or 4250	125	≥50,000	-
61529	<a href="#">RDORKIT5AS/034UNVD840/24U/WH</a>	25, 30 or 34	120-277	0-10	840	3100, 3750 or 4250	125	≥50,000	-
61530	<a href="#">RDORKIT5AS/034UNVD850/24U/WH</a>	25, 30 or 34	120-277	0-10	850	3100, 3750 or 4250	125	≥50,000	-
61531	<a href="#">RDORKIT5AS/045UNVD835/24U/WH</a>	34, 38 or 45	120-277	0-10	835	4250, 4750 or 5600	125	≥50,000	-
61532	<a href="#">RDORKIT5AS/045UNVD840/24U/WH</a>	34, 38 or 45	120-277	0-10	840	4250, 4750 or 5600	125	≥50,000	-
61533	<a href="#">RDORKIT5AS/045UNVD850/24U/WH</a>	34, 38 or 45	120-277	0-10	850	4250, 4750 or 5600	125	≥50,000	-
61534	<a href="#">RDORKIT5AS/030UNVD835/14U/WH</a>	20, 25 or 30	120-277	0-10	835	2500, 3125 or 3750	125	≥50,000	-
61535	<a href="#">RDORKIT5AS/030UNVD840/14U/WH</a>	20, 25 or 30	120-277	0-10	840	2500, 3125 or 3750	125	≥50,000	-
61536	<a href="#">RDORKIT5AS/030UNVD850/14U/WH</a>	20, 25 or 30	120-277	0-10	850	2500, 3125 or 3750	125	≥50,000	-
61696	<a href="#">RDORKIT5AS/030UNVD835/22U/WH/E</a>	20, 25 or 30	120-277	0-10	835	2500, 3125 or 3750	125	≥50,000	E
61697	<a href="#">RDORKIT5AS/030UNVD840/22U/WH/E</a>	20, 25 or 30	120-277	0-10	840	2500, 3125 or 3750	125	≥50,000	E
61698	<a href="#">RDORKIT5AS/030UNVD85/022U/WH/E</a>	20, 25 or 30	120-277	0-10	850	2500, 3125 or 3750	125	≥50,000	E
61699	<a href="#">RDORKIT5AS/034UNVD835/24U/WH/E</a>	25, 30 or 34	120-277	0-10	835	3100, 3750 or 4250	125	≥50,000	E
61700	<a href="#">RDORKIT5AS/034UNVD840/24U/WH/E</a>	25, 30 or 34	120-277	0-10	840	3100, 3750 or 4250	125	≥50,000	E
61701	<a href="#">RDORKIT5AS/034UNVD850/24U/WH/E</a>	25, 30 or 34	120-277	0-10	850	3100, 3750 or 4250	125	≥50,000	E
61702	<a href="#">RDORKIT5AS/045UNVD835/24U/WH/E</a>	34, 38 or 45	120-277	0-10	835	4250, 4750 or 5600	125	≥50,000	E
61703	<a href="#">RDORKIT5AS/045UNVD840/24U/WH/E</a>	34, 38 or 45	120-277	0-10	840	4250, 4750 or 5600	125	≥50,000	E
61704	<a href="#">RDORKIT5AS/045UNVD850/24U/WH/E</a>	34, 38 or 45	120-277	0-10	850	4250, 4750 or 5600	125	≥50,000	E
61705	<a href="#">RDORKIT5AS/030UNVD835/14U/WH/E</a>	20, 25 or 30	120-277	0-10	835	2500, 3125 or 3750	125	≥50,000	E
61706	<a href="#">RDORKIT5AS/030UNVD840/14U/WH/E</a>	20, 25 or 30	120-277	0-10	840	2500, 3125 or 3750	125	≥50,000	E
61707	<a href="#">RDORKIT5AS/030UNVD850/14U/WH/E</a>	20, 25 or 30	120-277	0-10	850	2500, 3125 or 3750	125	≥50,000	E



# ValueLED™ Lumen Selectable Volumetric Troffer Product Offering

Item Number	Ordering Abbreviation	Wattage	Voltage	Dimming	CRI/CCT	Lumens	LPW	Lifetime	Option
61512	<u>VOLUME5AS/030UNVD835/22U/WH</u>	20, 25 or 30	120-277	0-10	835	2500, 3125 or 3750	125	≥50,000	-
61513	<u>VOLUME5AS/030UNVD840/22U/WH</u>	20, 25 or 30	120-277	0-10	840	2500, 3125 or 3750	125	≥50,000	-
61514	<u>VOLUME5AS/030UNVD850/22U/WH</u>	20, 25 or 30	120-277	0-10	850	2500, 3125 or 3750	125	≥50,000	-
61515	<u>VOLUME5AS/034UNVD835/24U/WH</u>	25, 30 or 34	120-277	0-10	835	3100, 3750 or 4250	125	≥50,000	-
61516	<u>VOLUME5AS/034UNVD840/24U/WH</u>	25, 30 or 34	120-277	0-10	840	3100, 3750 or 4250	125	≥50,000	-
61517	<u>VOLUME5AS/034UNVD850/24U/WH</u>	25, 30 or 34	120-277	0-10	850	3100, 3750 or 4250	125	≥50,000	-
61518	<u>VOLUME5AS/045UNVD835/24U/WH</u>	34, 38 or 45	120-277	0-10	835	4250, 4750 or 5600	125	≥50,000	-
61519	<u>VOLUME5AS/045UNVD840/24U/WH</u>	34, 38 or 45	120-277	0-10	840	4250, 4750 or 5600	125	≥50,000	-
61520	<u>VOLUME5AS/045UNVD850/24U/WH</u>	34, 38 or 45	120-277	0-10	850	4250, 4750 or 5600	125	≥50,000	-
61521	<u>VOLUME5AS/030UNVD835/14U/WH</u>	20, 25 or 30	120-277	0-10	835	2500, 3125 or 3750	125	≥50,000	-
61522	<u>VOLUME5AS/030UNVD840/14U/WH</u>	20, 25 or 30	120-277	0-10	840	2500, 3125 or 3750	125	≥50,000	-
61523	<u>VOLUME5AS/030UNVD850/14U/WH</u>	20, 25 or 30	120-277	0-10	850	2500, 3125 or 3750	125	≥50,000	-
61684	<u>VOLUME5AS/030UNVD835/22U/WH/E</u>	20, 25 or 30	120-277	0-10	835	2500, 3125 or 3750	125	≥50,000	E
61685	<u>VOLUME5AS/030UNVD840/22U/WH/E</u>	20, 25 or 30	120-277	0-10	840	2500, 3125 or 3750	125	≥50,000	E
61686	<u>VOLUME5AS/030UNVD850/22U/WH/E</u>	20, 25 or 30	120-277	0-10	850	2500, 3125 or 3750	125	≥50,000	E
61687	<u>VOLUME5AS/034UNVD835/24U/WH/E</u>	25, 30 or 34	120-277	0-10	835	3100, 3750 or 4250	125	≥50,000	E
61688	<u>VOLUME5AS/034UNVD840/24U/WH/E</u>	25, 30 or 34	120-277	0-10	840	3100, 3750 or 4250	125	≥50,000	E
61689	<u>VOLUME5AS/034UNVD850/24U/WH/E</u>	25, 30 or 34	120-277	0-10	850	3100, 3750 or 4250	125	≥50,000	E
61690	<u>VOLUME5AS/045UNVD835/24U/WH/E</u>	34, 38 or 45	120-277	0-10	835	4250, 4750 or 5600	125	≥50,000	E
61691	<u>VOLUME5AS/045UNVD840/24U/WH/E</u>	34, 38 or 45	120-277	0-10	840	4250, 4750 or 5600	125	≥50,000	E
61692	<u>VOLUME5AS/045UNVD850/24U/WH/E</u>	34, 38 or 45	120-277	0-10	850	4250, 4750 or 5600	125	≥50,000	E
61693	<u>VOLUME5AS/030UNVD835/14U/WH/E</u>	20, 25 or 30	120-277	0-10	835	2500, 3125 or 3750	125	≥50,000	E
61694	<u>VOLUME5AS/030UNVD840/14U/WH/E</u>	20, 25 or 30	120-277	0-10	840	2500, 3125 or 3750	125	≥50,000	E
61695	<u>VOLUME5AS/030UNVD850/14U/WH/E</u>	20, 25 or 30	120-277	0-10	850	2500, 3125 or 3750	125	≥50,000	E

## ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer Family Overview

---



- Both the UltraLED Retrofit Doorkits and Volumetric Troffers will continue to be offered.
- These families continue to offer 347-480V as well as controls options with ENLIGHTED, LUTRON, AND ENCELIUM.



# ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer Nomenclature Review

## Ordering Guide

RDORKIT	5A	S	/ XX	UNX	D	8	XX	/ XX	U	/ WH	-
Product Name	Generation	Lumen Selectable	Wattage	Voltage	Dimming	CRI	Color Temp	Size	Mounting	Color/Finish	Options
RDORKIT =	5A =	S =	30 = 20, 25, or 30W	UNV =	D = 0-10V	8 = >80	35 = 3500K	14 = 1x4 ft	U = Universal	WH = White	Blank = no option
Retrofit Doorkit	Generation 5A	Lumen Selectable	34 = 25, 30, or 34W	120-277V			40 = 4000K	22 = 2x2 ft	Mounting		E = Emergency Battery Back-up
			45 = 34, 38, or 45W				50 = 5000K	24 = 2x4 ft			

## Ordering Guide

VOLUME	5A	S	/ XX	UNX	D	8	XX	/ XX	U	/ WH	-
Product Name	Generation	Lumen Selectable	Wattage	Voltage	Dimming	CRI	Color Temp	Size	Mounting	Color/Finish	Options
VOLUME =	5A =	S =	30 = 20, 25, or 30W	UNV =	D = 0-10V	8 = >80	35 = 3500K	14 = 1x4 ft	U = Universal	WH = White	Blank = no option
Volumetric Troffer	Generation 5A	Lumen Selectable	34 = 25, 30, or 34W	120-277V			40 = 4000K	22 = 2x2 ft	Mounting		E = Emergency Battery Back-up
			45 = 34, 38, or 45W				50 = 5000K	24 = 2x4 ft			



## ValueLED™ Lumen Selectable Retrofit Doorkit and Volumetric Troffer

### Key Takeaways

---

- Application : The ValueLED Retrofit Doorkit and Volumetric Troffer are offered in three sizes (1'x4', 2'x2', and 2'x4'). The addition of the 1'x4' options fills an existing gap in our current portfolio
- All models are DLC Premium listed to maximize rebate opportunities
- The lumen selectability feature allows for a wide range of lumen output options with fewer NAEDs, reducing the complexity of inventory management

---

**THANK YOU**