

Push-Fit Medium Bi-Pin Fluorescent Lamp Lampholders (Pin Mount)

APPLICATION and PERFORMANCE SPECIFICATION

Description: T8/T12 Lampholder Shunted and Non-Shunted Version

- Pin Support System for reliable lamp pin support
- Body: PC Face: PBT GF; Shunted version body of PBT GF
- Base or lateral push-in terminals:
- For wall thickness up to 1.2mm (0.047")
- 660W / 600V
- UL Temperature Rating T 120
- Shunted models ①compliant

Type	Ref. #	Lampholder Thickness (mm)	Spring Adj.	Push-In Terminals	Internal Shunting	Drawing	Weight (g)	Packing Unit
49105	537166	13	-	Base	-	A	5.1	1000
49125	536329	13	-	Base	Shunted	A	5.2	1000
49106	537167	13	X	Base	-	B	5.9	1000
49126	536330	13	X	Base	Shunted	B	5	1000
59105	537182	13	-	Lateral	-	C	5	1000
59125	536345	13	-	Lateral	Shunted Right	C	5	1000
59145	536349	13	-	Lateral	Shunted Left	C	5	1000
59106	537183	13	X	Lateral	-	D	5	1000
59126	536346	13	X	Lateral	Shunted Right	D	5	1000
59146	536350	13	X	Lateral	Shunted Left	D	5	1000
49505	537174	9.5	-	Base	-	A	5	1000
49525	536337	9.5	-	Base	Shunted	A	5	1000
49506	537175	9.5	X	Base	-	B	5.5	1000
49526	536338	9.5	X	Base	Shunted	B	5.5	1000
59505	537206	9.5	-	Lateral	-	C	4.8	1000
59525	536369	9.5	-	Lateral	Shunted Right	C	4.8	1000
59545	536373	9.5	-	Lateral	Shunted Left	C	4.8	1000
59506	537207	9.5	X	Lateral	-	D	4.8	1000
59526	536370	9.5	X	Lateral	Shunted Right	D	4.8	1000
59546	536347	9.5	X	Lateral	Shunted Left	D	4.8	1000

Safety:

- cULus listed - Indoor Use (E110363)
- ENEC



Performance:

- Meets ANSI Standard C81.62-2009
- Meets IEC Standard 60400
- Lampholders meet IP20 standard

Warranty:

Universal Lighting Technologies warrants to the purchaser that each lampholder will be free from defects in material or workmanship for a period of 3 years from date of manufacture when properly installed and under normal conditions of use.

