

# G4, GX5.3, GY6.35 Push-fit System

## For Low-voltage Halogen Incandescent Lamps

Lampholders for lamps with base G4, GZ4,

G5.3, GX5.3, G6.35, GY6.35

All T ratings in this chapter refer to IEC standards

G/GZ4, G/GX5.3, G/GY6.35 lampholder

Casing: LCP, natural, multipoint contacts: CuNiZn

T270 (acc. to IEC), maximum operating temperature: 240°C


Nominal rating: 8A/24V (for G4 lamps: 4A/24V)

Push-In terminals for stranded leads with ferrule on bare end of core 1.4–1.8mm (0.056–0.071") dia. (also available with mounted leads)

Mounting holes for #4 screws (M3)

Weight: 2.2g, packing qty.: 1000 pcs.  
Type: 33300

**Ref. No.: 109547**



Cover caps with externally threaded body 20.8x2

for screw rings (see below)

To clip onto the lampholder 109547


Material: LCP, natural

Integrated moulded thread: M10x1

Weight: 4g, packing qty.: 1000 pcs.

Type: 97255

**Ref. No.: 109548**



Screw rings

For components with externally threaded body 20.8x2

Weight: 1.8g, packing qty.: 1000 pcs.

Type: 97257

**Ref. No.: 109550** PPS, black

**Ref. No.: 507490** LCP, natural

