

Lampholders with Separate Mounting Spring for GU4 Lamps

For Low-voltage Halogen Incandescent Lamps

Additional lead lengths and types upon request
All T ratings in this chapter refer to IEC standards

G/GZ4, G/GX5.3, G/GY6.35 lampholders

Casing: ceramic, Cover plate: mica

Contacts: Ni, T300 (acc. to IEC)

Nominal rating: 10A/24V

Leads: Cu nickel-plated, stranded conductors

18AWG, PTFE insulation, max. 250°C


Mounting holes for #4 screws (M3)

Weight: 8.1g, packing qty.: 1000 pcs.

Type: 32400

Ref. No.: 109855 lead length: 152mm (5.9")

Ref. No.: 109856 lead length: 300mm (11.8")



GU4 mounting spring for lamp

Material: stainless steel

The mounting spring has to be fastened with the lampholder type 32400.

The luminaire manufacturer is responsible for the attachment.

Weight: 1.6g, packing qty.: 1000 pcs.

Type: 32490

Weight: 1.6g, packing qty.: 1000 pcs.

Type: 32490

Ref. No.: 108678



G/GZ4, G/GX5.3, G/GY6.35 lampholder

Casing: LCP, natural

Multipoint contacts: CuNiZn, T270 (acc. to IEC)

Maximum operating temperature: 240°C

Nominal rating: 8A/24V (for G4 lamps: 4A/24V)

Push-In terminals for stranded leads with ferrule on bare end of core 1.4–1.8mm (0.055–0.071") dia.


(lampholder is also available with mounted cables)

Mounting holes for #4 screws (M3)

Weight: 2.2g, packing qty.: 1000 pcs., type: 33300

Weight: 2.2g, packing qty.: 1000 pcs., type: 33300

Ref. No.: 109547



GU4 mounting spring for lamp

Material: stainless steel

To clip onto the lampholder 109547

The luminaire manufacturer is responsible for the attachment.

Weight: 0.8g, packing qty.: 1000 pcs.

Type: 94095

Type: 94095

Ref. No.: 109553

