

Standard Ballasts

18–58 W, 230/240 V

For compact fluorescent lamps

Shape: 28x41 mm

Lamp				Ballast									Capacitor	
Output	Type	Base	Current	Type	Ref. No.	V, Hz	a	b	c	Weight	Δt/Δt _{an}	EEL*	C _P	Current
W			mA				mm	mm	mm	kg	K		μF	mA
230 V, 50 Hz														
36/40	T-U/TR	2G13/G10q	430	LN 36.570	169779	230, 50	150	140	92	0.80	35/90	B1	4.5	210
				LN 36.149	529029	230, 50	150	140	60	0.55	55/150	B2	4.5	210
				L 36.337**	508294	230, 50	150	140	53	0.50	60/160	—	4.5	210
38	TC-DD	GR10q	430	LN 36.570	169779	230, 50	155	140	92	0.80	35/90	B1	4.5	210
				LN 36.149	529029	230, 50	150	140	60	0.55	55/150	B2	4.5	210
				L 36.337**	508294	230, 50	150	140	53	0.50	60/160	—	4.5	210
58	T-U	2G13	670	LN 58.568	169389	230, 50	233	220	160	1.31	35/95	B1	7.0	320
				LN 58.189	537038	230, 50	190	180	100	0.87	50/135	B2	7.0	320
				LN 58.116	508186	230, 50	190	180	92	0.80	55/160	B2	7.0	320
				L 58.718**	169658	230, 50	190	180	92	0.80	60/170	—	7.0	320
240 V, 50 Hz														
18	TC-D/TC-T	G24d-2/GX24d-2	220	LN 18.234	538572	240, 50	85	75	27	0.28	65/155	B2	2.0	110
18	TC-F/TC-L	2G10/2G11	370	LN 18.507	164566	240, 50	155	140	92	0.80	35/60	B1	4.5	120
				LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B2	4.5	120
				L 18.936**	534627	240, 50	150	140	45	0.43	70/140	—	4.5	120
18	T-U	2G13	370	LN 18.507	164566	240, 50	155	140	92	0.80	35/60	B1	4.5	120
				LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B2	4.5	120
				L 18.936**	534627	240, 50	150	140	45	0.43	70/140	—	4.5	190
2x18	TC-F/TC-L	2G10/2G11	400	LN 2x18.135	535778	240, 50	150	140	45	0.43	65	B1	4.0	210
				L 36/40.443	530008	240, 50	150	140	60	0.55	65/155	B1	4.0	210
				LN 36.201	527196	240, 50	150	140	62	0.55	55/140	B1	4.0	210
				LN 36.505	164555	240, 50	155	140	92	0.80	40/95	B1	4.0	210
24	TC-F/TC-L	2G10/2G11	345	LN 18.507	164566	240, 50	155	140	92	0.80	35/60	B1	4.5	150
				LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B2	4.5	150
				L 18.936**	534627	240, 50	150	140	45	0.43	70/140	—	4.5	150
26	TC-D/TC-T	G24d-3/GX24d-3	325	LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B1	4.5	150
				LN 26.140	508909	240, 50	105	95	53	0.50	55/145	B2	3.5	140
				L 18.936**	534627	240, 50	150	140	45	0.43	70/140	—	3.5	140
28	TC-DD	GR8/GR10q	320	LN 18.162	533043	240, 50	150	140	60	0.55	60/110	B1	3.5	150
				L 18.936**	534627	240, 50	150	140	45	0.43	70/140	—	3.5	150
32	T-R	G10q	450	LN 36.505	164555	240, 50	155	140	92	0.80	40/95	B1	4.0	220
36	TC-F/TC-L	2G10/2G11	430	LN 36.505	164555	240, 50	155	140	92	0.80	40/95	B1	4.5	210
				LN 36.201	527196	240, 50	155	140	62	0.55	55/140	B2	4.5	210
				L 36/40.443**	164438	240, 50	150	140	60	0.55	65/155	—	4.5	210
36/40	T-U/TR	2G13/G10q	430	LN 36.505	164555	240, 50	155	140	92	0.80	40/95	B1	4.5	210
				LN 36.201	527196	240, 50	150	140	62	0.55	55/140	B2	4.5	210
				L 36/40.443**	164438	240, 50	150	140	60	0.55	65/155	—	4.5	210
38	TC-DD	GR10q	430	LN 36.201	527196	240, 50	150	140	62	0.55	55/140	B2	4.5	210
				L 36/40.443**	164438	240, 50	150	140	60	0.55	65/155	—	4.5	210
58	T-U	2G13	670	LN 58.506	164560	240, 50	233	220	160	1.31	35/85	B1	7.0	320
				LN 58.190	537056	240, 50	190	180	100	0.87	50/150	B2	7.0	320
				LN 58.722	534252	240, 50	190	180	92	0.80	60/180	B2	7.0	320

* Energy efficiency: EEl=B2 and EEl=B1, valid until 2017

** Ballasts without CE mark for markets outside of the EU