

Super-thin Ballasts 5–40 W, 220 V

For compact fluorescent lamps

Shape: 18x41 mm

Lamp				Ballast									Capacitor	
Output	Type	Base	Current	Type	Ref. No.	V, Hz	a	b	c	Weight	Δt/Δt _{an}	EEL*	C _p	Current
W			mA				mm	mm	mm	kg	K		μF	mA
220 V, 60 Hz														
5	TC-S	G23	180	L 7/9/11.134	163041	220, 60	155	140	58	0.37	45/65	—	2.0	70
2x5	TC-S	G23	180	L 13.164	163162	220, 60	155	140	58	0.37	40/80	—	2.0	90
7	TC-S	G23	175	L 7/9/11.134	163041	220, 60	155	140	58	0.37	45/65	—	2.0	70
2x7	TC-S	G23	160	L 13.164	163162	220, 60	155	140	58	0.37	40/80	—	2.0	90
9	TC-S	G23	170	L 7/9/11.134	163041	220, 60	155	140	58	0.37	45/65	—	2.0	70
2x9	TC-S	G23	140	L 13.164	163162	220, 60	155	140	58	0.37	40/80	—	2.0	90
10	TC-D	G24d-1	190	L 13.164	163162	220, 60	155	140	58	0.37	40/80	—	2.0	80
11	TC-S	G23	155	L 7/9/11.134	163041	220, 60	155	140	58	0.37	45/65	—	2.0	80
13	TC-D/TC-T	G24d-1/GX24d-1	175	L 13.164	163162	220, 60	155	140	58	0.37	40/80	—	2.0	110
16	TC-DD	GR8/GR10q	195	L 16.202	163235	220, 60	155	140	58	0.37	45/110	—	2.0	100
18	TC-F/TC-L	2G10/2G11	370	L 18.140	163045	220, 60	195	180	116	0.64	55/80	—	4.0	150
18	T-U	2G13	370	L 18.140	163045	220, 60	195	180	116	0.64	55/80	—	4.0	150
2x18	TC-F/TC-L	2G10/2G11	400	L 36.188	163218	220, 60	195	180	116	0.64	45/110	—	4.0	210
24	TC-F/TC-L	2G10/2G11	345	L 18.140	163045	220, 60	195	180	116	0.64	55/80	—	4.0	190
26	TC-D/TC-T	G24d-3/GX24d-3	325	L 18.140	163045	220, 60	195	180	116	0.64	55/80	—	3.0	160
28	TC-DD	GR8/GR10q	320	L 18.140	163045	220, 60	195	180	116	0.64	55/80	—	3.0	155
36	TC-F/TC-L	2G10/2G11	430	L 36.188	163218	220, 60	195	180	116	0.64	45/110	—	4.0	210
36/40	T-U/TR	2G13/G10q	430	L 36.188	163218	220, 60	195	180	116	0.64	45/110	—	4.0	220
38	TC-DD	GR10q	430	L 36.188	163218	220, 60	195	180	116	0.64	45/110	—	4.0	220

* Energy efficiency: EEL=B2 and EEL=B1, valid until 2017