



Description

Venture's LED Vapor fixtures are designed for use in harsh environments. Optimal for parking driver lane compliance. For use as utility lighting, parking garage and tunnels, maintenance areas.

Construction

The fixture is a Makrolon all plastic non-corrosive construction with a one piece fixture housing and lens. Chemical resistance information for Makrolon can be downloaded from the user manual tab on our website. The diffuse gasketed polycarbonate lens is secured by non-corrosive plastic clips. These versatile fixtures are IP-65 rated for use in variety of unique applications. Knock-out locations are available on both sides of the fixture as well as on top of the fixture as well.

Electrical

Fixtures are provided with 120-277V 50/60 Hz drivers with 0-10V DC dimming as a standard.

Mounting

Fixtures are supplied with surface mounting clips and V-Hooks for chain mounting. The lightweight design allows for easy installation/replacement of existing fixtures.

DLC Model# VP2-56NA-BF1

Product Performance

Wattage	55W
Lumen Output	7200
Correlated Color Temperature (CCT)	4000K
Color Rendering Index (CRI)	80+
Lumen Maintenance @50,000 hours*	86%
Calculated L70 @ 25°C Ambient in Hours*	108,000
Operating Temperature Range	-40°F to 104°F (-40°C to 40°C)

Physical Characteristics

Fixture Color	Gray
Width	6.6"
Length	50.2"
Height	3.7"

Electrical Characteristics

Amperage Draw (Input Volts/Amps)	120/0.47 208/0.28 240/0.24 277/0.21
----------------------------------	-------------------------------------

Regulatory Qualifications

cULus Listed

Suitable for wet locations

IP Rating - IP65

Accessories

Surface mount clips and V-Hook for dual point chain or cable hanging included

SP12714 - 120-277V Surge Protector

PH58143 - Wet Rated Motion Only Control Sensor - Long Extension

PH52171 - Wet Rated Motion/Photocell/Dimming Control Sensor - Long Extension

NOTE:

*Lumen maintenance data is based on LED testing per IESNA LM-80-08 and projected per IESNA TM-21-11



Venture LED Vapor Tight

