



VPL100MVHUD-A-4C-xxx

Driver Type	Constant Current Programmable LED Driver
No. of Channels	4
Input Voltage	120-277 V
Input Frequency	50-60 Hz
Dimming	ProDim: 0-10V and 3 level Dual Relay

Features

- Universal Voltage (120-277V)
- Multiple Output Channels
- Constant Current
- Programmable Wattage and Drive Current
- ProDim: 0-10V and 3 level Dual Relay
- Integrates with Adaptive Lighting Control Systems
- Compatible with LED modules and Coretech LED tubes
- UL, cUL, UL8750 Class 2
- FCC Part 15 Class A




CoreTech VPL

PRODUCT SPECIFICATIONS


OUTPUT		
No. of Channels	3	4
No. of Coretech LED Lamps	3	4
Output Voltage (Range)	25-50VDC	
Output Current Range (Programmable @ full load)	200mA - 500mA	
Total Rated Power	80W	

INPUT	
Frequency	50-60Hz
Input Voltage (range)	120-277 VAC
Power Factor (min.)	0.9 @ full load 277VAC
THD (max.)	20% @ full load 110AC
Efficiency (typical)	0.86

Wiring diagram



Dimension



Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.

Espen Technology, Inc. | 12257 Florence Avenue | Santa Fe Springs, CA 90670 | Phone: (562) 529-2938 | Fax: (562) 529-2978
Toll Free: (866) 933-7736 | Email: info@espentech.com | www.espentech.com