

## VTS-2-F32T8 FIX SUNL (NO BALLAST)



### Vapor Tight Slim Standard, 120V NO Ballast

#### Specifications

- Enclosed and gasketed housing will withstand most critical environments.
  - Weather and chemical resistant, corrosion free, and impervious to vapors, dust, and moisture. For wet locations.
  - Available in lengths of 4' or 8' (nominal)
  - Surface, stem or chain mountable
- Applications: Food handling and processing facilities, refrigerated storage, drug and chemical plants. Use in shower areas, parking garages, pedestrian and roadway tunnels, and outdoor public areas.



#### General Characteristics

<b>Material</b>	Plastic
<b>Lens Finish</b>	Clear
<b>Bulb</b>	T8
<b>Finish</b>	White
<b>Safety Rating</b>	ETL Listed

#### Fixture Characteristics

<b>Collection</b>	Bypass
<b>Shape</b>	Linear
<b>Number of Lights</b>	2 - Light
<b>Bulb Max Wattage</b>	32 Max
<b>Mounting</b>	Surface
<b>Use Location</b>	Indoor

#### Electrical Characteristics

<b>Watts</b>	2x 32
<b>Volts</b>	Multi-Volt

#### Product Dimensions

<b>Size</b>	48"
<b>Item Dimensions (in)</b>	(W) 6.80 (H) 4.35 (D) 51.70

#### Product Data

<b>Item Number</b>	92733-SU
<b>Barcode on SKU</b>	653703927336
<b>Brand</b>	SUNLITE
<b>Description</b>	VTS-2-F32T8