T-1¾ WEDGE BASE SINGLE CHIP LEDs

ORDERING INFORMATION: WB871 WC 1 - 24V/25
(A) (B) (C) (D)

(A) MODEL
WB871

(B) LED LENS COLOR
WC = WATER CLEAR

(C) LED EMITTING COLOR & WAVELENGTH
1 = ULTRA RED (660nm)
2 = STD. RED (630-635nm)
U2 = ULTRA HI EFF. RED (623-630nm)
3 = STD. ORANGE (605-610nm)
U3 = ULTRA ORANGE (612-620nm)
4 = STD. YELLOW (585nm)
*S4 = ULTRA YELLOW (590-595nm)
5 = STD. GREEN (565-570nm)
*6NW = ULTRA PURE GREEN (520-530nm)
*8NW = FLUORESCENT "WHITE" (NO nm VALUE)
*10NW = ULTRA BLUE (465-475nm)
*11NW = BLUISH GREEN (498-508nm)
*12NW = SOFT WHITE (NO nm VALUE)
***Max. Continuous current 10mA.**

MODEL: WB871



(D) STANDARD DC & AC OPERATING VOLTAGES/mA
5V/25, 12V/25, 24V/25, 28V/25, 36V/12, 48V/12 & 60V/12
APPLICATION MUST BE SPECIFIED WHEN ORDERING:
VAC = ALTERNATING CURRENT VDC(V) = DIRECT CURRENT
Note: Please call factory for other voltages.

DIRECT INCANDESCENT LAMP REPLACEMENTS
17, 18, 56, 74, 79, 84, 85, 86, ETC...

HOUSING MAT'L. UL94-VO APPROVED

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

1050 E. DOMINGUEZ ST. UNIT P * CARSON, CA 90746 * TEL: (310) 603-0403 * FAX: (310) 603-1335