



T-1³/₄ WEDGE BASE SINGLE CHIP LEDs

ORDERING INFORMATION:

WB871 WC 2 - 24V/25
(A) (B) (C) (D)

(A) MODEL

WB871

WBF871 (FLAT-TOP)

(B) LED LENS COLOR

WC = WATER CLEAR

(C) LED EMITTING COLOR & WAVELENGTH

1 = ULTRA RED (660nm) **OBSOLETE**

2 = STD. RED (630-635nm)

U2 = ULTRA HI EFF. RED (623-630nm)

3 = STD. ORANGE (605-610nm)

U3 = ULTRA ORANGE (612-620nm)

4 = STD. YELLOW (585nm)

*S4 = ULTRA YELLOW (590-595nm)

5 = STD. GREEN (565-570nm)

*6NW = ULTRA PURE GREEN (520-530nm)

*8NW = FLUORESCENT "WHITE" (NO nm VALUE)

*10NW = ULTRA BLUE (465-475nm)

*12NW = SOFT WHITE (NO nm VALUE)

*Max. Continuous current 10mA.

(D) STANDARD DC & AC OPERATING VOLTAGES/mA

5V/25, 12V/25, 24V/25, 28V/25, 36V/12, 48V/12 & 60V/12

APPLICATION MUST BE SPECIFIED WHEN ORDERING:

VAC = ALTERNATING CURRENT VDC(V) = DIRECT CURRENT

Note: Please call factory for other voltages.


DIRECT INCANDESCENT LAMP REPLACEMENTS

17, 18, 56, 74, 79, 84, 85, 86, ETC...

HOUSING MAT'L. UL94-V0 APPROVED

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

MODEL: WB871



MODEL: WBF871

