WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

Rubix

Wall Mount 3000K

Model & Size	*Color Temp & CRI*	*Watt*	*Lumens*	*Finish*
❍ WS-W2509	❍ 3000K 90	16W	805	❍ AL Brushed Aluminum
❍ WS-W2510	❍ 3000K 90	30W	1385	❍ BK Black
				❍ BZ Bronze
				❍ GH Graphite
				❍ WT White

Example: **WS-W2509-AL**

DESCRIPTION

Available in single and twin light configurations, this die-cast aluminum LED wall luminaire is Wet Location listed for a broad range of exterior lighting applications. Designed with a square profile, this version of Rubix mounts upwards or downwards.

FEATURES

- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast Aluminum
Power:	30W, 16W
Input:	120-277 VAC, 50/60Hz
Dimming:	ELV: 100-15%, 0-10V: 100-10%
Light Source:	Integrated LED
Rated Life:	70000 Hours
Mounting:	Mounts directly to junction box, Can be mounted on wall in all orientations
Finish:	Electrostatically Powder Coated White, Bronze, Brushed Aluminum, Black, Graphite
Operating Temp:	-40°F to 122°F (-40°C to 50°C)
Standards:	UL, cUL, Wet Location Listed, IP65, Title 24 JA8-2016 Compliant, ADA

FINISHES

Black | Bronze | Brushed Aluminum | Graphite | White

LINE DRAWING



WS-W2509



WS-W2510